

Lifting Beam T-A-VR

Product information



The lifting beam of the T-A-VR series has an eye suspension for single hooks according to DIN 15401 on the crane side and adjustable lifting frames on the load side. The matching shackles are included in the scope of delivery. You are able to expand the lifting beam with additional equipment from our web shop. The lifting beam is supplied in the standard color RAL 3000 (flame red), other colors are also possible on request.

For other intermediate sizes and load capacities, you can also send us an inquiry [... Read more](#)

Material: Construction steel

Marking: According to standard, CE-marked


Temperature range: -20°C up to +100°C

Finish: RAL 3000 (flame red)

Standard: EN 13155

Lifting Beam T-A-VR

Blueprint



Lifting Beam T-A-VR

Technical data

Part code	WLL ton	Length m	H, in	L min. mm in	L max. mm in	S in	T in	Wmm in	Weight kg
6205TAVR22000	2	1-2	5.31	39.37	78.74	1.97	0.79	2.56	53
6205TAVR32000	3	1-2	5.91	39.37	78.74	3.94	0.98	2.95	76
6205TAVR23000	2	1.5-3	5.31	55.12	118.11	1.97	0.79	2.56	100
6205TAVR52000	5	1-2	6.69	39.37	78.74	3.94	0.98	3.35	105
6205TAVR24000	2	2-4	5.31	78.74	157.48	1.97	0.79	2.56	127
6205TAVR33000	3	1.5-3	5.91	59.06	118.11	3.94	0.98	2.95	131
6205TAVR82000	8	1-2	8.27	39.37	78.74	3.94	1.18	4.13	151
6205TAVR102000	10	1-2	9.45	39.37	78.74	3.94	1.57	4.72	157
6205TAVR34000	3	2-4	5.91	78.74	157.48	3.94	0.98	2.95	165
6205TAVR53000	5	1.5-3	6.69	59.06	118.11	3.94	0.98	3.35	167
6205TAVR25000	2	2.5-5	5.31	98.43	196.85	1.97	0.79	2.56	197
6205TAVR83000	8	1.5-3	8.27	59.06	118.11	3.94	1.18	4.13	222
6205TAVR26000	2	3-6	5.31	118.11	236.22	1.97	0.79	2.56	229
6205TAVR35000	3	2.5-5	5.91	98.43	196.85	3.94	0.98	2.95	246
6205TAVR54000	5	2-4	6.69	78.74	157.48	3.94	0.98	3.35	249
6205TAVR103000	10	1.5-3	9.45	59.06	118.11	3.94	1.57	4.72	252
6205TAVR36000	3	3-6	5.91	118.11	236.22	3.94	0.98	2.95	297
6205TAVR84000	8	2-4	8.27	78.74	157.48	3.94	1.18	4.13	326
6205TAVR104000	10	2-4	9.45	78.74	157.48	3.94	1.57	4.72	349
6205TAVR55000	5	2.5-5	6.69	98.43	196.85	3.94	0.98	3.35	363
6205TAVR85000	8	2.5-5	8.27	98.43	196.85	3.94	1.18	4.13	424
6205TAVR56000	5	3-6	6.69	118.11	236.22	3.94	0.98	3.35	426
6205TAVR105000	10	2.5-5	9.45	98.43	196.85	3.94	1.57	4.72	524
6205TAVR86000	8	3-6	8.27	118.11	236.22	3.94	1.18	4.13	642
6205TAVR106000	10	3-6	9.45	118.11	236.22	3.94	1.57	4.72	670