

S-3 Webbing slings with triangles

Product information



This professional webbing sling is extremely suitable for intensive industrial use.

Properties

- Duplex version; double band layer.
- WLL stripes, each stripe is 1 ton.
- Every 30 mm band width is 1 ton load capacity.

... [Read more](#)

Marking: According to standard, CE-marked

Standard: EN 1677-1, EN 1492-1

Note: Packed in plastic including REMA manual.

S-3 Webbing slings with triangles

Technical data

Part code	GTIN No.	WLL ton	EWL m	Basket Hitch 0-45° ton	Basket Hitch 45°-60° ton	WLL 45-60° t	Webbing width mm	Colour	Weight kg
34111213031	8717365004773	1	1	1.4	1	1	30	Violet	1.18
34111213035	8717365004780	1	2	1.4	1	1	30	Violet	1.56
34111213037	8717365004797	1	3	1.4	1	1	30	Violet	1.94
34111213061	8717365004872	2	1	2.8	2	2	60	Green	2
34111213039	8717365004803	1	4	1.4	1	1	30	Violet	2.32
34111213065	8717365004889	2	2	2.8	2	2	60	Green	2.6
34111213041	8717365004810	1	5	1.4	1	1	30	Violet	2.7
34111213043	8717365004827	1	6	1.4	1	1	30	Violet	3.08
34111213067	8717365004896	2	3	2.8	2	2	60	Green	3.2
34111213045	8717365004834	1	7	1.4	1	1	30	Violet	3.46
34111213069	8717365004902	2	4	2.8	2	2	60	Green	3.8
34111213047	8717365004841	1	8	1.4	1	1	30	Violet	3.84
34111213049	8717365004858	1	9	1.4	1	1	30	Violet	4.22
34111213071	8717365004919	2	5	2.8	2	2	60	Green	4.4
34111213091	8717365004971	3	1	4.2	3	3	90	Yellow	4.45
34111213051	8717365004865	1	10	1.4	1	1	30	Violet	4.6
34111213073	8717365004926	2	6	2.8	2	2	60	Green	5
34111213095	8717365004988	3	2	4.2	3	3	90	Yellow	5.2
34111213075	8717365004933	2	7	2.8	2	2	60	Green	5.6
34111213097	8717365004995	3	3	4.2	3	3	90	Yellow	5.95
34111213077	8717365004940	2	8	2.8	2	2	60	Green	6.2
34111213099	8717365005008	3	4	4.2	3	3	90	Yellow	6.7
34111213079	8717365004957	2	9	2.8	2	2	60	Green	6.8
34111213125	8717365005077	4	2	5.6	4	4	120	Grey	7
34111213081	8717365004964	2	10	2.8	2	2	60	Green	7.4
34111213101	8717365005015	3	5	4.2	3	3	90	Yellow	7.45
34111213103	8717365005022	3	6	4.2	3	3	90	Yellow	8.2
34111213127	8717365005084	4	3	5.6	4	4	120	Grey	8.2
34111213105	8717365005039	3	7	4.2	3	3	90	Yellow	8.95
34111213129	8717365005091	4	4	5.6	4	4	120	Grey	9.4
34111213155	8717365005169	5	2	7	5	5	150	Red	9.6

S-3 Webbing slings with triangles

Technical data

Part code	GTIN No.	WLL ton	EWL m	Basket Hitch 0-45° ton	Basket Hitch 45°-60° ton	WLL 45-60° t	Webbing width mm	Colour	Weight kg
34111213107	8717365005046	3	8	4.2	3	3	90	Yellow	9.7
34111213109	8717365005053	3	9	4.2	3	3	90	Yellow	10.45
34111213131	8717365005107	4	5	5.6	4	4	120	Grey	10.6
34111213111	8717365005060	3	10	4.2	3	3	90	Yellow	11.2
34111213157	8717365005176	5	3	7	5	5	150	Red	11.4
34111213133	8717365005114	4	6	5.6	4	4	120	Grey	11.8
34111213135	8717365005121	4	7	5.6	4	4	120	Grey	13
34111213159	8717365005183	5	4	7	5	5	150	Red	13.2
34111213137	8717365005138	4	8	5.6	4	4	120	Grey	14.2
34111213161	8717365005190	5	5	7	5	5	150	Red	15
34111213139	8717365005145	4	9	5.6	4	4	120	Grey	15.4
34111213141	8717365005152	4	10	5.6	4	4	120	Grey	16.6
34111213163	8717365005206	5	6	7	5	5	150	Red	16.8
34111213165	8717365005213	5	7	7	5	5	150	Red	18.6
34111213167	8717365005220	5	8	7	5	5	150	Red	20.4
34111213169	8717365005237	5	9	7	5	5	150	Red	22.2
34111213171	8717365005244	5	10	7	5	5	150	Red	24