

1 leg REMA-10- RML-RCX-RCH

Product information



The [Rema® 10 assortment](#) offers versatile chain sling solutions, allowing you to easily create one, two, three, or four-legged chain sling assemblies. Each component is designed for durability and can be delivered and replaced individually when needed.

1 leg REMA-10 | masterlink RML | connecting link RCX | clevis sling hook RCH



Each component of this chain sling assembly carries the distinctive **H-84** mark certified by the [German DGUV](#), ensuring a testament to its exceptional quality. [... Read more](#)

Marking: According to standard, CE-marked

Standard: EN 1677-1, DIN 17115, DIN 5692, EN 818-7

Safety factor: 4

Grade: 10

1 leg REMA-10- RML-RCX-RCH

Technical data

Part code	GTIN No.	Chain diameter mm	WLL ton	EWL m	Model	Weight kg
240526911061	8717365150722	6	1.4	1	1400KG-6MM-RML-RCH-1M	1.7
2405269110615	8717365150739	6	1.4	1.5	1400KG-6MM-RML-RCH-1,5M	2.1
240526911062	8717365150746	6	1.4	2	1400KG-6MM-RML-RCH-2M	2.5
2405269110625	8717365150753	6	1.4	2.5	1400KG-6MM-RML-RCH-2,5M	2.9
240526911063	8717365150760	6	1.4	3	1400KG-6MM-RML-RCH-3M	3.3
2405269110635	8717365150777	6	1.4	3.5	1400KG-6MM-RML-RCH-3,5M	3.7
240526911064	8717365150784	6	1.4	4	1400KG-6MM-RML-RCH-4M	4.1
240526911081	8717365150791	8	2.5	1	2500KG-8MM-RML-RCH-1M	2.9
2405269110815	8717365150807	8	2.5	1.5	2500KG-8MM-RML-RCH-1,5M	3.65
240526911082	8717365150814	8	2.5	2	2500KG-8MM-RML-RCH-2M	4.4
2405269110825	8717365150821	8	2.5	2.5	2500KG-8MM-RML-RCH-2,5M	5.15
240526911083	8717365150838	8	2.5	3	2500KG-8MM-RML-RCH-3M	5.9
2405269110835	8717365150845	8	2.5	3.5	2500KG-8MM-RML-RCH-3,5M	6.65
240526911084	8717365150852	8	2.5	4	2500KG-8MM-RML-RCH-4M	7.4
240526911101	8717365150869	10	4	1	4000KG-10MM-RML-RCH-1M	4.6
2405269111015	8717365150876	10	4	1.5	4000KG-10MM-RML-RCH-1,5M	5.75
240526911102	8717365150883	10	4	2	4000KG-10MM-RML-RCH-2M	6.9
2405269111025	8717365150890	10	4	2.5	4000KG-10MM-RML-RCH-2,5M	8.05
240526911103	8717365150906	10	4	3	4000KG-10MM-RML-RCH-3M	9.2
2405269111035	8717365150913	10	4	3.5	4000KG-10MM-RML-RCH-3,5M	10.35
240526911104	8717365150920	10	4	4	4000KG-10MM-RML-RCH-4M	11.5
240526911131	8717365150937	13	6.7	1	6700KG-13MM-RML-RCH-1M	8.6
2405269111315	8717365150944	13	6.7	1.5	6700KG-13MM-RML-RCH-1,5M	10.6
240526911132	8717365150951	13	6.7	2	6700KG-13MM-RML-RCH-2M	12.6
2405269111325	8717365150968	13	6.7	2.5	6700KG-13MM-RML-RCH-2,5M	14.6
240526911133	8717365150975	13	6.7	3	6700KG-13MM-RML-RCH-3M	16.6
2405269111335	8717365150982	13	6.7	3.5	6700KG-13MM-RML-RCH-3,5M	18.6
240526911134	8717365150999	13	6.7	4	6700KG-13MM-RML-RCH-4M	20.6
240526911161	8717365151002	16	10	1	10T-16MM-RML-RCH-1M	13.8
2405269111615	8717365151019	16	10	1.5	10T-16MM-RML-RCH-1,5M	16.8
240526911162	8717365151026	16	10	2	10T-16MM-RML-RCH-2M	19.8

1 leg REMA-10- RML-RCX-RCH

Technical data

Part code	GTIN No.	Chain diameter mm	WLL ton	EWL m	Model	Weight kg
2405269111625	8717365151033	16	10	2.5	10T-16MM-RML-RCH-2,5M	22.8
240526911163	8717365151040	16	10	3	10T-16MM-RML-RCH-3M	25.8
2405269111635	8717365151057	16	10	3.5	10T-16MM-RML-RCH-3,5M	28.8
240526911164	8717365151064	16	10	4	10T-16MM-RML-RCH-4M	31.8