

Chain sling assy 3-leg REMA-10-RMA-RDG-RCH

Product information



The [Rema® 10 assortment](#) offers versatile chain sling solutions, allowing you to easily create one, two, three, or four-legged chain sling assemblies. Each component is designed for durability and can be delivered and replaced individually when needed.

3-leg REMA-10 chain | masterlink RML | clevis shortening hook RDG | clevis sling hook RCH



Each component of this chain sling assembly carries the distinctive **H-84** mark certified by the [German DGUV](#), ensuring a testament to its exceptional quality. [... Read more](#)

Marking: According to standard, CE-marked

Standard: EN 818-7, EN 1677-1, DIN 17115, DIN 5692

Safety factor: 4

Grade: 10

Chain sling assy 3-leg REMA-10-RMA-RDG-RCH

Technical data

Part code	GTIN No.	Chain diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t	Model	Weight kg
241126933061	8717365154225	6	2.94	1	2.94	2,1	2940KG-6MM-RMA-RDG-RCH-1M	5.9
2411269330615	8717365154232	6	2.94	1.5	2.94	2,1	2940KG-6MM-RMA-RDG-RCH-1,5M	7.1
241126933062	8717365154249	6	2.94	2	2.94	2,1	2940KG-6MM-RMA-RDG-RCH-2M	8.3
2411269330625	8717365154256	6	2.94	2.5	2.94	2,1	2940KG-6MM-RMA-RDG-RCH-2,5M	9.5
241126933063	8717365154263	6	2.94	3	2.94	2,1	2940KG-6MM-RMA-RDG-RCH-3M	10.7
2411269330635	8717365154270	6	2.94	3.5	2.94	2,1	2940KG-6MM-RMA-RDG-RCH-3,5M	11.9
241126933064	8717365154287	6	2.94	4	2.94	2,1	2940KG-6MM-RMA-RDG-RCH-4M	13.1
241126933081	8717365154294	8	5.25	1	5.25	3,75	5250KG-8MM-RMA-RDG-RCH-1M	11.4
2411269330815	8717365154300	8	5.25	1.5	5.25	3,75	5250KG-8MM-RMA-RDG-RCH-1,5M	13.65
241126933082	8717365154317	8	5.25	2	5.25	3,75	5250KG-8MM-RMA-RDG-RCH-2M	15.9
2411269330825	8717365154324	8	5.25	2.5	5.25	3,75	5250KG-8MM-RMA-RDG-RCH-2,5M	18.15
241126933083	8717365154331	8	5.25	3	5.25	3,75	5250KG-8MM-RMA-RDG-RCH-3M	20.4
2411269330835	8717365154348	8	5.25	3.5	5.25	3,75	5250KG-8MM-RMA-RDG-RCH-3,5M	22.65
241126933084	8717365154355	8	5.25	4	5.25	3,75	5250KG-8MM-RMA-RDG-RCH-4M	24.9
241126933101	8717365154362	10	8.4	1	8.4	6	8400KG-10MM-RMA-RDG-RCH-1M	19.5
2411269331015	8717365154379	10	8.4	1.5	8.4	6	8400KG-10MM-RMA-RDG-RCH-1,5M	22.95
241126933102	8717365154386	10	8.4	2	8.4	6	8400KG-10MM-RMA-RDG-RCH-2M	26.4
2411269331025	8717365154393	10	8.4	2.5	8.4	6	8400KG-10MM-RMA-RDG-RCH-2,5M	29.85
241126933103	8717365154409	10	8.4	3	8.4	6	8400KG-10MM-RMA-RDG-RCH-3M	33.3
2411269331035	8717365154416	10	8.4	3.5	8.4	6	8400KG-10MM-RMA-RDG-RCH-3,5M	36.75
241126933104	8717365154423	10	8.4	4	8.4	6	8400KG-10MM-RMA-RDG-RCH-4M	40.2
241126933131	8717365154430	13	14	1	14	10,05	14T-13MM-RMA-RDG-RCH-1M	34
2411269331315	8717365154447	13	14	1.5	14	10,05	14T-13MM-RMA-RDG-RCH-1,5M	40
241126933132	8717365154454	13	14	2	14	10,05	14T-13MM-RMA-RDG-RCH-2M	46
2411269331325	8717365154461	13	14	2.5	14	10,05	14T-13MM-RMA-RDG-RCH-2,5M	52
241126933133	8717365154478	13	14	3	14	10,05	14T-13MM-RMA-RDG-RCH-3M	58
2411269331335	8717365154485	13	14	3.5	14	10,05	14T-13MM-RMA-RDG-RCH-3,5M	64
241126933134	8717365154492	13	14	4	14	10,05	14T-13MM-RMA-RDG-RCH-4M	70
241126933161	8717365154508	16	21	1	21	15	21T-16MM-RMA-RDG-RCH-1M	57.4
2411269331615	8717365154515	16	21	1.5	21	15	21T-16MM-RMA-RDG-RCH-1,5M	66.4
241126933162	8717365154522	16	21	2	21	15	21T-16MM-RMA-RDG-RCH-2M	75.4

Chain sling assy 3-leg REMA-10-RMA-RDG-RCH

Technical data

Part code	GTIN No.	Chain diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t	Model	Weight kg
2411269331625	8717365154539	16	21	2.5	21	15	21T-16MM-RMA-RDG-RCH-2,5M	84.4
241126933163	8717365154546	16	21	3	21	15	21T-16MM-RMA-RDG-RCH-3M	93.4
2411269331635	8717365154553	16	21	3.5	21	15	21T-16MM-RMA-RDG-RCH-3,5M	102.4
241126933164	8717365154560	16	21	4	21	15	21T-16MM-RMA-RDG-RCH-4M	111.4