CERTEX | Lifting Solutions Group
Axel Johnson International

CBV beam lifting clamps

Product information

REMA®

Designed for safe lifting and transportation of steel beams in vertical position.

Properties

- The lifting eye is placed as far as possible in the center of gravity of the beam to be hoisted

Application

- For vertical lifting, transportation and stacking of steel (H) beams, profiles and structures where the load must stay perfectly in position
- Especially recommended for transportation and stacking of steel (H) beams (e .g . when sawing of steel beams, stacking of steel beams and building of steel constructions)
- Jaw openings available from: 0 to 25 mm.

... *Read more*

Marking: According to standard, CE-marked
Standard: EN 12100, EN 13155
Note: The plate surface of the material must have a hardness level of max. HrC 37/345 Hb
Warning: Minimum weight to be lifted is 10% of the safe workload.

Safety factor: 5

© October 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

CBV beam lifting clamps

Blueprint



Technical data

Part code	GTIN No.	WLL ton	Jaw width mm	Model	A in	B in	C in	D, in	E in	F in	G, in	H, in	Weight kg
50213313000	8717365015205	1	0-15	CBV-1.0	0-0.59	6.89	5.91	8.9	1.38	5.12	1.38	1.85	4
50213313001	8717365015212	2	0-20	CBV-2.0	0-0.79	10.43	7.87	13.58	2.36	6.5	2.2	2.64	8
50213313002	8717365023101	3	0-25	CBV-3.0	0-0.98	12.8	9.25	16.14	2.83	7.56	3.03	2.56	16

© October 2026 - All Rights Reserved