

Hoist traverse beam REMA, with 2 adjustable hooks.

Product information



Properties

- Surface finish: zinc phosphate primer RAL 2004 (orange).
- Capacity range labelling.
- Black-and-yellow safety markings at beam ends.
- Hooks equipped with safety latches.
- High quality steel hooks grade 10.

Option

- Sandblasting and painting in every RAL color.
- Higher load capacity and bigger dimensions on request.

[... Read more](#)




Marking: According to standard, CE-marked

Standard: EN 1677-1, EN 12100, EN 13155

Hoist traverse beam REMA, with 2 adjustable hooks.

Blueprint



Technical data

Part code	GTIN No.	WLL ton	Model	B2mm in	C in	D, in	H, in	L in	n x kmm in	Weight kg
62053962041	8717365017841	1	TRA-VE-1000-1M	5.51	3.35	2.17	14.96	39.37	0.08	30
62053962043	8717365017858	1	TRA-VE-1000-1,6M	5.51	3.35	2.17	15.75	62.99	0.12	40
62053962049	8717365017889	1.6	TRA-VE-1600-1,6M	5.91	3.35	2.17	18.9	62.99	0.08	48
62053962045	8717365017865	1	TRA-VE-1000-2,5M	6.3	3.35	2.17	16.54	98.43	0.2	67
62053962051	8717365017896	1.6	TRA-VE-1600-2,5M	6.69	3.35	2.17	19.69	98.43	0.16	83
62053962047	8717365017872	1	TRA-VE-1000-3,15M	6.69	3.35	2.17	16.54	124.02	0.28	100
62053962057	8717365017926	2.5	TRA-VE-2500-2,5M	7.09	3.35	2.76	21.26	98.43	0.16	115
62053962053	8717365017902	1.6	TRA-VE-1600-3,15M	7.48	3.35	2.17	20.47	124.02	0.2	120
62053962059	8717365017933	2.5	TRA-VE-2500-3,15M	7.87	3.35	2.76	22.05	124.02	0.2	140
62053962055	8717365017919	1.6	TRA-VE-1600-4M	7.87	3.35	2.17	20.47	157.48	0.28	171
62053962061	8717365017940	2.5	TRA-VE-2500-4M	8.66	3.35	2.76	22.83	157.48	0.28	202
62053962063	8717365017957	2.5	TRA-VE-2500-5M	9.45	3.35	2.76	23.62	196.85	0.31	284