

Aluminum Lever Hoist Powertex PALH-S1

Product information



POWERTEX

Extremely small and lightweight aluminum lever hoist. It weighs only approximately 50% of a similar standard lever hoist. The hoist can be used for lifting as well as pulling. 250 kg-750 kg hoists are delivered with a handy carrying/belt bag.

Features:

- Safe - Each hoist is dynamic proof load tested 1,5 x WLL before leaving the factory
- Compact, lightweight construction with aluminum covers
- Durable construction with powder coated finish and plated frame parts
- Lever hoist is chromium 6 free
- Sealed bearings inside maximize efficiency and serviceability.
- Sprocket wheel surface treated against wear and corrosion
- Safe and well covered automatic load reaction break
- Equipped with double brake pawls
- Fine calibrated Electro Galvanized (European made) load chain for smooth operation
- Swivel hooks at both ends makes in line positioning easy
- Hooks are designed to open at overload instead of breaking
- Hooks fitted with heavy duty steel safety latches
- Hook have Deformation Check Dots forged into side for overload detection
- RFID equipped (chip) for easy service and inspection
- QR code for on-site access to Multilanguage user manuals

• Test certificates and Declaration of Conformity enclosed with each hoist. [... Read more](#)

Material: Durable aluminium/steel construction, rubber handle

Marking: According to standard, CE-marked, Powertex, Model, WLL, Chain type, Serial number, User manual/QR code

Temperature range: -10°C up to +50°C


Finish: White powder coated body, side plate assembly and hooks black powder coated

Standard: EN 13157, EN 818-7

Safety factor: 4:1

Aluminum Lever Hoist Powertex PALH-S1

Blueprint



Technical data

Part code	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Hand force max. kg	a in	b mm in	c in	d mm in	e mm in	f mm in	g mm in	s mm in	t in	Weight kg
500500030150460	0.25	1.5	1	PALH-S1/250KG	3 x 9	29	3.43	2.68	7.87	5.71	2.19	1.4	0.83	1.26	0.43	1.45
500500030300460	0.25	3	1	PALH-S1/250KG	3 x 9	29	3.43	2.68	7.87	5.71	2.19	1.4	0.83	1.26	0.43	1.95
500500050150460	0.5	1.5	1	PALH-S1/500KG	4 x 12	27	3.96	3.19	9.84	6.3	2.46	1.65	0.96	1.36	0.47	2.5
500500050300460	0.5	3	1	PALH-S1/500KG	4 x 12	27	3.96	3.19	9.84	6.3	2.46	1.65	0.96	1.36	0.47	3.3
500500080150460	0.75	1.5	1	PALH-S1/750KG	5 x 15	33	4.13	3.62	10.24	7.09	2.52	1.65	1.12	1.4	0.55	3.4
500500080300460	0.75	3	1	PALH-S1/750KG	5 x 15	33	4.13	3.62	10.24	7.09	2.52	1.65	1.12	1.4	0.55	4.3
500500150150460	1.5	1.5	1	PALH-S1/1500KG	7,1 x 20,1	42	4.8	4.29	12.99	8.66	2.7	2.05	1.38	1.67	0.85	6.27
500500150300460	1.5	3	1	PALH-S1/1500KG	7,1 x 20,1	42	4.8	4.29	12.99	8.66	2.7	2.05	1.38	1.67	0.85	8.2
500500300150460	3	1.5	2	PALH-S1/3000KG	7,1 x 20,1	43	4.8	6.3	17.01	8.66	2.7	2.44	1.69	1.97	0.96	9.11
500500300300460	3	3	2	PALH-S1/3000KG	7,1 x 20,1	43	4.8	6.3	17.01	8.66	2.7	2.44	1.69	1.97	0.96	12.4